

TRAVELMAP

MY AIR PROTECTOR TL30 | TL30A
Technical Datasheet



	TL30	TL30A
UV-C-LED		
Wavelength	265 – 285 nm	265 – 285 nm
Filters		
Coarse particle filter *	✓	✓
Fine particle filter **	Optionally	Optionally
Volumetric flow <i>Accuracy ± 10%</i>		
Without filter (Fan)	30 m³/h	30 m³/h
Coarse particle filter *	25 m³/h	25 m³/h
Fine particle filter **	20 m³/h	20 m³/h
Noise emission <i>Accuracy ± 2 dB(A)</i>		
Noise level ***	40 dB(A)	40 dB(A)
Battery (Li Ion)		
Battery capacity	-	10,4 Ah
Runtime	-	up to 4h
Power supply connection		
Electrical connection	220 – 240 V 50/60 Hz	220 – 240 V 50/60 Hz
Power	60 W	60 W
Current	5 A	5 A
Car adapter connection		
Electrical connection	12 V	12 V
Fuse	3 A	3 A
Dimensions / Weight		
Weight	1 kg	1,5 kg
Dimensions L x W x H	255 x 244 x 70	255 x 244 x 70

* Filter class: ISO 16890 (COARSE 40%) (Similar old standard EN 779 Filter class G2)

** Filter class: ISO 16890 (COARSE 80%) (Similar old standard EN 779 Filter class G4)

*** Sound pressure level at 1 m distance according to DIN EN ISO 11203, Base noise level of 30 dB(A)

Information provided without guarantee. Mistakes and changes reserved. Status 09/2021